



11 mm EZ Bend™ PMI® Hudson Classic Professional Rope Rope | Static Rope



The “time tested” burly sheath design of PMI®’s 11 mm Classic Static makes it a world favorite for professionals who must routinely subject their ropes to high abrasion applications. No other 11 mm rope will outlast a PMI® Classic in side by side, real world applications except a PMI® Max-Wear rope.

Key Features

- NFPA Certified
 - Third party certified by UL (Underwriters Laboratories)
 - Also available in custom colors & lengths
 - 16 carrier construction
 - Torsionally balanced, continuous filament nylon
 - EZ-Bend construction
 - CI 1801
 - Available in many colors
-

Additional Information

Shipping weight | N/A

Color | Arc Yellow/black, Black, Blue/black, Orange/black, Red/black, Solid Blue, Solid Red, White/black

Length | 100 ft (30 meters), 150 ft (46 meters), 200 ft (61 meter), 300 ft (92 meters), 600 ft (183 meters), 656 ft (200 meters), 1200 ft (366 meters)

Weight | 80 g/m

MBS | 32.7 kN (7344 lbf)

Knotability | 0.9

Shrinkage | 3.2%

Sheath Content | 50.4%

Elongation at 300 lbf | 1.6%

Elongation at 600 lbf | 3.0%

Elongation at 1000 lbf | 5.8%

Elongation at 1800 lbf | 8.8%

Elongation at 10% MBS | 3.4-4.4%

Compliant | ANSI Z359.15 (2014), EN 1891-A, NFPA 1983 (2017), T

Tags

[fall protection](#), [made in USA](#), [Rope Rescue](#), [Arborist](#), [Confined Space](#), [Rope Access](#), [Tower Work](#), [Fire Rescue](#), [Wilderness Rescue](#), [Ropes Course](#), [Cave Rescue](#), [Utilities Safety](#), [NFPA Certified](#), [Third party certified by UL](#), [16-carrier sheath construction](#), [Available in custom colors & lengths](#)

Product Code

RR110BL092E | Solid Blue | 300 ft (92 meters)
RR110BL183E | Solid Blue | 600 ft (183 meters)
RR110BK200E | Black | 656 ft (200 meters)
RR110BB030E | Blue/black | 100 ft (30 meters)
RR110BB046E | Blue/black | 150 ft (46 meters)
RR110BB061E | Blue/black | 200 ft (61 meter)
RR110BB092E | Blue/black | 300 ft (92 meters)
RR110BB183E | Blue/black | 600 ft (183 meters)
RR110BB200E | Blue/black | 200 ft (61 meter)
RR110BK030E | Black | 100 ft (30 meters)
RR110BK046E | Black | 150 ft (46 meters)
RR110BK061E | Black | 200 ft (61 meter)
RR110BK092E | Black | 300 ft (92 meters)
RR110BK183E | Black | 600 ft (183 meters)
RR110BL030E | Solid Blue | 100 ft (30 meters)
RR110BL046E | Solid Blue | 150 ft (46 meters)

RR110BL061E | Solid Blue | 200 ft (61 meter)
RR110OB046E | Orange/black | 150 ft (46 meters)
RR110OB030E | Orange/black | 100 ft (30 meters)
RR110BL200E | Solid Blue | 656 ft (200 meters)
RR110OB061E | Orange/black | 200 ft (61 meter)
RR110OB092E | Orange/black | 300 ft (92 meters)
RR110OB183E | Orange/black | 600 ft (183 meters)
RR110OB200E | Orange/black | 656 ft (200 meters)
RR110RB030E | Red/black | 100 ft (30 meters)
RR110RB046E | Red/black | 150 ft (46 meters)
RR110RB061E | Red/black | 200 ft (61 meter)
RR110RB092E | Red/black | 300 ft (92 meters)
RR110RB183E | Red/black | 600 ft (183 meters)
RR110RB200E | Red/black | 656 ft (200 meters)
RR110RD030E | Solid Red | 100 ft (30 meters)
RR110RD046E | Solid Red | 150 ft (46 meters)
RR110RD061E | Solid Red | 200 ft (61 meter)
RR110RD092E | Solid Red | 300 ft (92 meters)
RR110RD183E | Solid Red | 600 ft (183 meters)
RR110RD200E | Solid Red | 656 ft (200 meters)
RR110WB030E | White/black | 100 ft (30 meters)
RR110WB046E | White/black | 150 ft (46 meters)
RR110WB061E | White/black | 200 ft (61 meter)
RR110WB092E | White/black | 300 ft (92 meters)
RR110WB183E | White/black | 600 ft (183 meters)
RR110WB200E | White/black | 656 ft (200 meters)
RR110WB366E | White/black | 1200 ft (366 meters)
RR110YB030E | Arc Yellow/black | 100 ft (30 meters)
RR110YB046E | Arc Yellow/black | 150 ft (46 meters)
RR110YB061E | Arc Yellow/black | 200 ft (61 meter)
RR110YB092E | Arc Yellow/black | 300 ft (92 meters)
RR110YB183E | Arc Yellow/black | 600 ft (183 meters)
RR110YB200E | Arc Yellow/black | 656 ft (200 meters)

