



UTILITY LOOPS



Designed for placing protection when climbing structures, our Utility Loops support versatile anchor building. These sewn slings are made from 1-inch (25-mm) mil-spec tubular web for high strength and good grip when tied off with a girth hitch, the minimum breaking strength (loop) is 24 kN (5,400 lbf).

About CMC Web Gear

CMC sewn web products reflect many years of manufacturing experience and designs based on field use, rescues and testing. Lightweight yet durable, our tubular web delivers a high strength-to-weight ratio. Each product is sewn in our own California manufacturing facility with contrasting color thread for ease of inspection. We build CMC Web Gear as if we were going to use it ourselves – and we do.

Option	Small
Item	201212
PRODUCT WEIGHT	2.1 OZ (60 G)
LENGTH	24 IN (61 CM)
COLOR	BLUE
MBS	24 KN (5,400 LBF)

Option	Medium
Item	201213
PRODUCT WEIGHT	2.9 OZ (82 G)
LENGTH	36 IN (91 CM)
COLOR	ORANGE
MBS	24 KN (5,400 LBF)

Option	Large
Item	201214
PRODUCT WEIGHT	4.6 OZ (130 G)
LENGTH	60 IN (152 CM)
COLOR	RED
MBS	24 KN (5,400 LBF)
