



## STATIC-PRO™ LIFELINE

An extremely low-stretch kernmantle rescue lifeline constructed of 100% High Tenacity Polyester (HTP) fiber. The polyester fibers do not absorb water, so there is no loss of strength or increase in weight if the rope gets wet. With less than 2% stretch at 300 lbf, Static-Pro is an excellent choice for high lines, long rappels, and many mechanical advantage haul systems. Polyester fiber ropes have better resistance to acids than nylon, which makes Static-Pro the preferred choice in acidic environments. Favored for its excellent hand, knotability and UV resistance, Static-Pro Lifelines come in solid colors with a single stripe to prevent confusion with CMC Lifeline and other solid color kernmantle ropes.

Rope is sold by the foot. Rope ends are included. No charge on custom cutting. Specify desired lengths in order notes. See table below for maximum lengths.

### Static-Pro™ Lifeline Specifications

The following specifications apply to all diameters of CMC Static-Pro Lifeline:

**Certification** — UL Classified to NFPA 1983 Standard on Life Safety Rope and Equipment for Emergency Services, 2017 Edition.

**Construction** — Block creel, static kernmantle.

**Fiber** — 100% High Tenacity Polyester (HTP).

**Sheath** — 32-strand braided, with half the strands having a left (Z) twist and the other half having a right (S) twist for a balanced, torque-free rope with maximum abrasion resistance.

**Rating** — NFPA General Use for 12.5 mm (1/2 in); NFPA Technical Use for 11 mm (7/16 in)

**Temperature** — Melt point 480° F (249° C).

Made in the U.S.A.

*\*Weight of rope is measured per 100 feet.*

<b>Option</b>	Blue, 7/16
<b>Item</b>	281102
<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	6.5 LB (2.9 KG)
<b>DIAMETER</b>	11 MM (7/16 IN)
<b>COLOR / STRIPE</b>	BLUE / WHITE
<b>NFPA RATING</b>	TECHNICAL USE
<b>3 SIGMA MBS</b>	35 KN (7,868 LBF)

<b>MAX LENGTH</b>	762 M (2,500 FT)
<b>Option</b>	Orange, 7/16
<b>Item</b>	281103
<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	6.5 LB (2.9 KG)
<b>DIAMETER</b>	11 MM (7/16 IN)
<b>COLOR / STRIPE</b>	ORANGE / WHITE
<b>NFPA RATING</b>	TECHNICAL USE
<b>3 SIGMA MBS</b>	35 KN (7,868 LBF)
<b>MAX LENGTH</b>	762 M (2,500 FT)
<b>Option</b>	Red, 7/16
<b>Item</b>	281109
<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	6.5 LB (2.9 KG)
<b>DIAMETER</b>	11 MM (7/16 IN)
<b>COLOR / STRIPE</b>	RED / WHITE
<b>NFPA RATING</b>	TECHNICAL USE
<b>3 SIGMA MBS</b>	35 KN (7,868 LBF)
<b>MAX LENGTH</b>	762 M (2,500 FT)
<b>Option</b>	White, 1/2
<b>Item</b>	281200
<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	8.5 LB (3.9 KG)
<b>DIAMETER</b>	12.5 MM (1/2 IN)
<b>COLOR / STRIPE</b>	WHITE / BLUE
<b>NFPA RATING</b>	GENERAL USE
<b>3 SIGMA MBS</b>	41 KN (9,217 LBF)
<b>MAX LENGTH</b>	549 M (1,800 FT)
<b>Option</b>	Orange, 1/2
<b>Item</b>	281201

<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	8.5 LB (3.9 KG)
<b>DIAMETER</b>	12.5 MM (1/2 IN)
<b>COLOR / STRIPE</b>	ORANGE / WHITE
<b>NFPA RATING</b>	GENERAL USE
<b>3 SIGMA MBS</b>	41 KN (9,217 LBF)
<b>MAX LENGTH</b>	549 M (1,800 FT)

---

**Option** Blue, 1/2

**Item** 281202

<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	8.5 LB (3.9 KG)
<b>DIAMETER</b>	12.5 MM (1/2 IN)
<b>COLOR / STRIPE</b>	BLUE / WHITE
<b>NFPA RATING</b>	GENERAL USE
<b>3 SIGMA MBS</b>	41 KN (9,217 LBF)
<b>MAX LENGTH</b>	549 M (1,800 FT)

---

**Option** Red, 1/2

**Item** 281203

<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	8.5 LB (3.9 KG)
<b>DIAMETER</b>	12.5 MM (1/2 IN)
<b>COLOR / STRIPE</b>	RED / WHITE
<b>NFPA RATING</b>	GENERAL USE
<b>3 SIGMA MBS</b>	41 KN (9,217 LBF)
<b>MAX LENGTH</b>	549 M (1,800 FT)

---

**Option** Yellow, 1/2

**Item** 281207

<b>SOLD</b>	BY THE FOOT
<b>WEIGHT PER 100 FT</b>	8.5 LB (3.9 KG)
<b>DIAMETER</b>	12.5 MM (1/2 IN)
<b>COLOR / STRIPE</b>	YELLOW / WHITE

**NFPA RATING**

GENERAL USE

**3 SIGMA MBS**

41 KN (9,217 LBF)

**MAX LENGTH**

549 M (1,800 FT)

---

1-800-235-5741

info@cmcpro.com

cmcpro.com