

CE

## MAILLON RAPIDE QUICK LINKS

Quick Links, or also commonly known as screw links, are gaining popularity for use in situations for which carabiners are not recommended, such as when tri-axial loading cannot be avoided. The Delta shape can be used to rig anchors. The Delta can be used as a chest harness connector. While slower to open and close than a carabiner, they can be more secure when tightened down — and they cost less.

## Working-At-Height / Industrial Rope Access / Technical Rope Rescue

Option	Delta, 6 mm
ltem	205002
PRODUCT WEIGHT	1.4 OZ (40 G)
BAR DIAMETER	6 M M
INSIDE LENGTH	1-3/4 IN (44 MM)
MATERIAL	STAINLESS STEEL
WORKING LOAD	4.4 KN (992 LBF)
BREAKING LOAD	22 KN (4950 LBF)
Option	Delta, 10 mm
Option Item	Delta, 10 mm 382101
ltem	382101
Item PRODUCT WEIGHT	382101 5.3 OZ (150 G)
ltem PRODUCT WEIGHT BAR DIAMETER	382101 5.3 OZ (150 G) 10 MM
Item PRODUCT WEIGHT BAR DIAMETER INSIDE LENGTH	382101 5.3 OZ (150 G) 10 MM 2-5/8 IN (67 MM)

Working at height requires reliable, quality equipment. The Maillon Rapide Quick Links can be used with confidence in work-atheight maneuvers for industrial rope access or technical rope rescue when used in accordance with the regulatory safety standards they fall under. Always use life safety equipment and gear according to the regulatory safety standards for which it is classified and/or certified.

BREAKING LOAD	44.1 KN (9,920 LBF)
Option	Delta, 12 mm
Item	382121
PRODUCT WEIGHT	9.1 OZ (258 G)
BAR DIAMETER	12 MM
INSIDE LENGTH	3-3/16 IN (81 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	10.8 KN (2,425 LBF)
BREAKING LOAD	53.9 KN (12,125 LBF)
Option	Oval, 5 mm
Item	383051
PRODUCT WEIGHT	1.3 OZ (37 G)
BAR DIAMETER	5 M M
INSIDE LENGTH	1-9/16 IN (40 MM)
MATERIAL	STAINLESS STEEL
WORKING LOAD	4.4 KN (992 LBF)
BREAKING LOAD	22.1 KN (4960 LBF)
Option	Oval, 7 mm
Item	383071
PRODUCT WEIGHT	1.8 OZ (51 G)
BAR DIAMETER	7 M M
INSIDE LENGTH	2-1/16 IN (52 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	5.4 KN (1,213 LBF)
BREAKING LOAD	27 KN (6,065 LBF)
Option	Oval, 12 mm
Item	383121
PRODUCT WEIGHT	8.2 OZ (233 G)
BAR DIAMETER	12 MM
INSIDE LENGTH	3-3/16 IN (81 MM)

MATERIAL	GALVANIZED STEEL
WORKING LOAD	14.7 KN (3,307 LBF)
BREAKING LOAD	73.6 KN (16,535 LBF)
Option	Long Oval, 10 mm
ltem	384101
PRODUCT WEIGHT	5.6 OZ (159 G)
BAR DIAMETER	10 MM
INSIDE LENGTH	3-3/8 IN (86 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	9.8 KN (2,205 LBF)
BREAKING LOAD	49 KN (11,025 LBF)

1-800-235-5741

info@cmcpro.com

cmcpro.com