





All CMC Lifeline is sold by the foot.

Featuring the optimum balance of strength, handling, and durability with minimum sheath slippage, this 100% nylon kernmantle rescue rope offers excellent knotability and provides a high level of control when used with a descent control device. The industry standard for those who prefer traditional nylon ropes, CMC Lifeline is a great choice whether you are a firefighter on a high-rise, performing a high-angle mountain rescue, responding to an industrial accident, or a tactical officer on rappel.

Rope is sold by the foot. Rope ends are included. No charge on custom cutting. Specify desired lengths in order notes. See table below for maximum lengths.

CMC Lifeline[™] Specifications

The following specifications apply to all diameters of CMC Lifeline:

Certification — UL Classified to NFPA 1983 Standard on Life Safety Rope and Equipment for Emergency Services, 2017 Edition. **Construction** — Block creel, static kernmantle.

Fiber — 100% nylon.

Sheath — 32-strand braided, with half the strands having a left (Z) twist and the other half having a right (S) twist for a balanced, torque-free rope with maximum abrasion resistance.

Rating — NFPA General Use for 13 mm (1/2 in) and 15.5 mm (5/8 in); NFPA Technical Use for 9.5 mm (3/8 in) and 11 mm (7/16 in) Temperature — Melt point 460° F (238° C).

Made in the USA

Certain products on this page have clearance pricing and are not able to be returned or exchanged.

Option	Orange, 7/16
ltem	272810
SOLD	BY THE FOOT
WEIGHT / 100 FT	2.5 KG (5.5 LB)
DIAMETER	11 MM (7/16 IN)
COLOR / STRIPE	ORANGE
NFPA RATING	TECHNICAL USE
3 SIGMA MBS	28 KN (6,294 LBF)

MAX LENGTH	427 M (1,400 FT)
Option	Red, 7/16
Item	272830
SOLD	BY THE FOOT
WEIGHT / 100 FT	2.5 KG (5.5 LB)
DIAMETER	11 MM (7/16 IN)
COLOR / STRIPE	RED
NFPA RATING	TECHNICAL USE
3 SIGMA MBS	28 KN (6,294 LBF)
MAX LENGTH	427 M (1,400 FT)
Option	Black, 7/16
ltem	272850
SOLD	BY THE FOOT
WEIGHT / 100 FT	2.5 KG (5.5 LB)
DIAMETER	11 MM (7/16 IN)
COLOR / STRIPE	BLACK
NFPA RATING	TECHNICAL USE
3 SIGMA MBS	28 KN (6,294 LBF)
MAX LENGTH	427 M (1,400 FT)
Option	White, 1/2
Item	263200
SOLD	BY THE FOOT
WEIGHT / 100 FT	3.5 KG (7.7 LB)
DIAMETER	13 MM (1/2 IN)
COLOR / STRIPE	WHITE
NFPA RATING	GENERAL USE
3 SIGMA MBS	42 KN (9,442 LBF)
MAX LENGTH	610 M (2,000 FT)
MAX LENGTH Option	610 M (2,000 FT) Orange, 1/2

SOLD	BY THE FOOT
WEIGHT / 100 FT	3.5 KG (7.7 LB)
DIAMETER	13 MM (1/2 IN)
COLOR / STRIPE	ORANGE
NFPA RATING	GENERAL USE
3 SIGMA MBS	42 KN (9,442 LBF)
MAX LENGTH	610 M (2,000 FT)
Option	Blue, 1/2
ltem	273220
SOLD	BY THE FOOT
WEIGHT / 100 FT	3.5 KG (7.7 LB)
DIAMETER	13 MM (1/2 IN)
COLOR / STRIPE	BLUE
NFPA RATING	GENERAL USE
3 SIGMA MBS	42 KN (9,442 LBF)
MAX LENGTH	610 M (2,000 FT)
MAX LENGTH Option	610 M (2,000 FT) Red, 1/2
,	
Option	Red, 1/2
Option	Red, 1/2 273230
Option Item SOLD	Red, 1/2 273230 BY THE FOOT
Option Item SOLD WEIGHT / 100 FT	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB)
Option Item SOLD WEIGHT / 100 FT DIAMETER	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN)
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING 3 SIGMA MBS	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE 42 KN (9,442 LBF)
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING 3 SIGMA MBS MAX LENGTH	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE 42 KN (9,442 LBF) 610 M (2,000 FT)
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING 3 SIGMA MBS MAX LENGTH Option	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE 42 KN (9,442 LBF) 610 M (2,000 FT)
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING 3 SIGMA MBS MAX LENGTH Option Item	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE 42 KN (9,442 LBF) 610 M (2,000 FT) Black, 1/2 273250
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING 3 SIGMA MBS MAX LENGTH Option Item SOLD	Red, 1/2 273230 BY THE FOOT 3.5 KG (7.7 LB) 13 MM (1/2 IN) RED GENERAL USE 42 KN (9,442 LBF) 610 M (2,000 FT) Black, 1/2 273250 BY THE FOOT

NFPA RATING	GENERAL USE
3 SIGMA MBS	42 KN (9,442 LBF)
MAX LENGTH	610 M (2,000 FT)
Option	Yellow, 1/2
ltem	273270
SOLD	BY THE FOOT
WEIGHT / 100 FT	3.5 KG (7.7 LB)
DIAMETER	13 MM (1/2 IN)
COLOR / STRIPE	YELLOW
NFPA RATING	GENERAL USE
3 SIGMA MBS	42 KN (9,442 LBF)
MAX LENGTH	610 M (2,000 FT)
MAX LENGTH Option	610 M (2,000 FT) Orange, 5/8
Option	Orange, 5/8
Option Item	Orange, 5/8 274010
Option Item SOLD	Orange, 5/8 274010 BY THE FOOT
Option Item SOLD WEIGHT / 100 FT	Orange, 5/8 274010 BY THE FOOT 5.0 KG (11.0 LB)
Option Item SOLD WEIGHT / 100 FT DIAMETER	Orange, 5/8 274010 BY THE FOOT 5.0 KG (11.0 LB) 15.5 MM (5/8 IN)
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE	Orange, 5/8 274010 BY THE FOOT 5.0 KG (11.0 LB) 15.5 MM (5/8 IN) ORANGE
Option Item SOLD WEIGHT / 100 FT DIAMETER COLOR / STRIPE NFPA RATING	Orange, 5/8 274010 BY THE FOOT 5.0 KG (11.0 LB) 15.5 MM (5/8 IN) ORANGE GENERAL USE

1-800-235-5741

info@cmcpro.com

cmcpro.com