

RESCUE PULLEYS







This lightweight, full-strength, Prusik-minding pulley is ideal for mountain rescue, swiftwater, or other technical teams where equipment weight is a significant consideration. By machining the side plates, the thickness of the metal can be varied to maximize the strength-to-weight ratio, a process that cannot be done with traditional bent metal side plates. Sealed ball bearings provide high efficiency and aluminum side plates protect the rope. An extremely low-profile stainless steel axle assembly reduces snagging on rocks, roots, and uneven surfaces. Designed for lifeline up to 1/2 inch (13 mm) in diameter. Available in Single or Double versions.

Do not load a single side only of a double sheave pulley.

Option	Single Rescue Pulley
Item	300301
TYPE	SINGLE SHEAVE
WEIGHT	145 G (5.1 OZ)
SHEAVE TREAD SIZE	38 X 13 MM (1.5 X .5 IN)
COLOR	RED
NFPA RATING	GENERAL USE
3 SIGMA MBS	52 KN (11,690 LBF)
Option	Double Rescue Pulley
Option	Double Rescue Pulley 300302
Item	300302
Item TYPE	300302 DOUBLE SHEAVE
Item TYPE WEIGHT	300302 DOUBLE SHEAVE 249 G (8.8 OZ)
TYPE WEIGHT SHEAVE TREAD SIZE	300302 DOUBLE SHEAVE 249 G (8.8 OZ) 38 X 13 MM (1.5 X .5 IN)

1-800-235-5741 info@cmcpro.com cmcpro.com