

DIMENSIONS & WEIGHTS	Capacity <i>lbs (kg)</i>	33 (15)	40 (18.5)	55 (25)	70 (30.5)
	Cylinder Diameter <i>inch (mm)</i>	24.4 (620)	24.4 (620)	27.6 (700)	30.1 (765)
	Cylinder Depth <i>inch (mm)</i>	16.4 (416)	21.6 (549)	23.1 (586)	23.5 (596)
	Cylinder Volume <i>cu ft</i>	4.5 (126)	6 (166)	8 (226)	9.7 (274)
	Net Weight <i>lbs (kg)</i>	525 (238)	562 (255)	741 (336)	899 (408)
	Crated Weight <i>lbs (kg)</i>	580 (263)	624 (283)	807 (366)	957 (434)
	Machine Width <i>inch (mm)</i>	29.5 (750)	29.5 (750)	34.3 (870)	34.3 (870)
	Machine Depth <i>inch (mm)</i>	32.25 (819)	41.8 (1063)	44.8 (1139)	46.2 (1174)
	Machine Height <i>inch (mm)</i>	52.9 (1344)	52.9 (1344)	56.1 (1424)	57.7 (1466)
	Door Opening <i>inch (mm)</i>	12.9 (327)	12.9 (327)	16.8 (426)	16.7 (424)
	Floor to Door <i>inch (mm)</i>	20 (509)	20 (509)	19.7 (500)	21.4 (544)
GENERAL	Shipping Dimensions <i>inch (mm)</i> (WxDxH)	30.6 x 37.9 x 58.8 (777 x 962 x 1494)	30.6 x 43.1 x 58.8 (777 x 1095 x 1494)	35.3 x 46.1 x 61.6 (897 x 1170 x 1565)	35.3 x 48.2 x 64.1 (897 x 1225 x 1627)
	Control Options	Logi Pro	Logi Pro	Logi Pro	Logi Pro
	Washing Speeds <i>rpm</i>	44	47	45	40
	Spin Speeds <i>rpm</i>	44/100/380/540/635/760	47/100/380/540/635/760	45/100/360/505/600/715	40/86/342/485/570/685
	G-force	50/100/140/200	50/100/140/200	50/100/140/200	50/100/140/200
	Drain Diameter <i>inch (mm)</i>	3 (80)	3 (80)	3 (80)	3 (80)
	Water Inlets <i>inch (mm)</i>	2 @ 3/4 (2 @ 19)	2 @ 3/4 (2 @ 19)	2 @ 3/4 (2 @ 19)	2 @ 3/4 (2 @ 19)
	Recommended Water Pressure <i>PSI (bar)</i>	30-60 (2-4)	30-60 (2-4)	30-60 (2-4)	30-60 (2-4)
	Water Flow <i>gal/min (l/min)</i>	16 (60)	16 (60)	16 (60)	16 (60)
	Total Power <i>kW</i>	0.85	0.8	1.05	1.3
CONNECTIONS					

* Product specifications and details are subject to change without notice. For the most current and complete technical specifications, architectural line drawings and warranty information, please visit www.cgilaundry.com.