

Sidewinder Compact® Angle Head Flashlight

FL1 STANDARD	C4 LED HIGH
	55 LUMENS
	5.25h
	69m
	1175 cd



Description: Ultra-compact, high performance, multi-source LED flashlight with C4® LED technology. This flashlight has been engineered to meet a variety of hands free task illumination requirements with various color LEDs operable at varying outputs and runtimes. The flashlight features a 185 degree tilting head and belt or web clip to allow positioning of the illumination source at the work area.

Military model features white, red, blue and IR LEDs
 Aviation model features white, green, blue and IR LEDs
 Medical model features white, red, green and IR LEDs
 Sportsman model features white, red, blue and green LEDs

Case Material: High impact super tough nylon case offers exceptional durability and weather resistance. All openings are O-ring sealed. Unbreakable polycarbonate lens with scratch resistant coating. Gasket sealed. Available in Coyote and OD Green.

Dims/Weight: Length: 3.00 in. (7.62 cm) Width: 1.00 in. (2.54 cm) Depth: 2.01 in. (5.11 cm)
 2.4 ounces (68 grams) with battery (included with purchase). 3.3 ounces (93 grams) with battery and optional helmet mount.

Light Source: High output C4 LED, white, shockproof with 50,000Hr lifetime/55 lumens, 1,175 candela peak beam intensity and 69m beam distance
 (See model for specific LED configuration)
 5mm IR LED, 880 nm peak wavelength, shockproof with 100,000Hr lifetime/25mW/sr (min) radiant intensity
 5mm Red LED, 630 nm peak wavelength, shockproof with 100,000Hr lifetime/1 lumen, 40 candela peak beam intensity and 13m beam distance
 5mm Blue LED, 470 nm peak wavelength, shockproof with 100,000Hr lifetime/ 1.8 lumens, 130 candela peak beam intensity and 23m beam distance
 5mm Green LED, 527 nm peak wavelength, shockproof with 100,000Hr lifetime/4.5 lumens, 68 candela peak beam intensity and 16m beam distance

On/Off/Intensity Mode Selection: Compound On-Off mode selector switch ergonomically separates On-ff-Dimming-Strobe and LED selection functions. Design does not require the operator to access separate switching locations on the device. Rubber dome actuator and 4 position pull-to-turn locking rotary selector knob with IR tactile indicator provides easy operation even when wearing heavy gloves.

Battery: One CR123A lithium cell provides fast replacement with readily available batteries. Allows for operation in extreme temperature environments (-40F to 150F)

Approvals: Meets applicable European Community Directives

Warranty: Streamlight warrants its Sidewinder Compact (excepting batteries) will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

SIDEWINDER COMPACT® LIGHT OUTPUT & BATTERY RUN TIME						
LED	Light Output	Low 5% Output	Medium 1 25% Output	Medium 2 60% Output	High 100% Output	Strobe 100% Output
C4*	55 Lumens	60 Hrs+	28 Hrs	9 Hrs	5.25 Hrs	9 Hrs
5mm IR	25mW/sr (min) radiant intensity	100 Hrs+	48 Hrs	24 Hrs	14 Hrs	24 Hrs
5mm Red	1 Lumens	100 Hrs+	48 Hrs	24 Hrs	14 Hrs	24 Hrs
5mm Blue	1.8 Lumens	100 Hrs+	36 Hrs	18 Hrs	10 Hrs	18 Hrs
5mm Green	4.5 Lumens	100 Hrs+	36 Hrs	18 Hrs	10 Hrs	18 Hrs

All runtime claims to 10% of initial output level. Illumination output electronically regulated.

Features:	Push button switch specified to 300K operations	3 meter multiple orientation impact resistance tested
	Pull-to-turn locking rotary knob prevents accidental mode changes	Cord attachment holes provided in battery compartment cover capable of supporting 25 lbs of load
	Push button switch enables/disables selected illumination source starting at low output and progressing to the brightest output in 4 discrete steps (Sportsman model enables selected illumination source starting at high output and progressing to the dimmest output). double-click of push button initiates high output strobe of selected illumination source.	Tactile battery polarity indicators for battery replacement in the dark. Built in battery polarity protection guards against damage to the light
	4 lighting sources: White C4 LED, IR LED (or Green), Red LED, Blue LED	Tethered battery compartment cap facilitates battery replacement in the dark without losing cap
	Double-click of button initiates high intensity strobe of selected light source	IPX7 Rated design; waterproof to 1 meter for 30 minutes. O-Ring and gasket sealed openings. Meets MIL-STD-810F, Method 512.4.



Item	UPC	Part #
Sportsman Model High Performance multi-source LED flashlight. Each LED features 4 levels of decreasing output intensities: High, Medium-High, Medium, Low, plus Strobe.		
Sidewinder Compact Sportsmans White C4 LED, Red, Blue, Green LEDs. Includes 1 lithium battery. Blister Packaged Coyote	080926-14132-2	14132
Military Model High Performance multi-source LED flashlight. Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe.		
Sidewinder Compact Military: White C4 LED, Red, Blue, IR LEDs. Includes helmet mount and 1 lithium battery. Blister Coyote	080926-14102-5	14102
Aviation Model High Performance multi-source LED flashlight. Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe.		
Sidewinder Compact Aviation: White C4 LED, Green, Blue, IR LEDs Includes helmet mount and 1 lithium battery. Boxed Coyote	080926-14120-9	14120
Medical Model High Performance multi-source LED flashlight. Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe.		
Sidewinder Compact Medical: White C4 LED, Red, Green, IR LEDs Includes elastic headstrap and helmet mount and 1 lithium battery. Boxed Coyote	080926-14140-7	14140
Sidewinder Compact Medical: White C4 LED, Red, Green, IR LEDs Includes helmet mount and 1 lithium battery. Boxed Coyote	080926-14141-4	14141
Sidewinder Helmet Mount Coyote	080926-14055-4	14055
Sidewinder Helmet Mount Green	080926-14056-1	14056
1913 rail mount adapter (for helmets) Coyote	080926-14057-8	14057
1913 rail mount adapter (for helmets) Green	080926-14058-5	14055
Replacement MOLLE retainer	080926-14030-1	14030
Sidewinder Helmet Mount Accessory Kit	080926-14112-4	14112
Sidewinder Rail Mount Accessory Kit	080926-14113-1	14113
Sidewinder Compact head strap Coyote	080926-14059-2	14059
Safety Wand Glow-in-the-Dark	080926-14902-1	14902
Lithium batteries (2) Pack	080926-85175-7	85175
Lithium batteries (12) Pack	080926-85177-1	85177
Lithium batteries (400) Pack	080926-85179-5	85179
Lithium batteries (6) Pack	080926-85180-1	85180

