

## PRODUCT FACT SHEET

## HID LITEBOX®

## RECHARGEABLE HIGH INTENSITY SEARCH LIGHT

**MARKET** 

APPLICATIONS: Fire & Rescue, Military, Utilities, Law Enforcement, Industrial Safety, Sporting Goods.

**DESCRIPTION:** The HID LiteBox® is a heavy-duty, rechargeable, completely portable high intensity search

light. It produces a focused beam of light measuring 1 Million candlepower that illuminates objects 1 mile away and ample peripheral illumination to light an entire scene. Integral Drings allow attachment of the included heavy duty shoulder strap. Included flood lens or

optional IR pass filter attaches to elastomer lens ring.

**CASE MATERIAL:** High-impact ABS thermoplastic housing. Elastomer impact bumper, lens ring and cushioned

grip/handle. Weatherproof construction.

**DIMENSIONS:** Length: 14.9 in. (38 cm) Body Width: 5.1 in. (13 cm) Overall Height: 8.8 in. (23 cm)

Head Diameter: 7.7 in. (20 cm)

**WEIGHT:** 10.1 lbs (4.6 kg) with battery (included in purchase).

**LENS:** Glass. Adhesive sealed to reflector.

**LIGHT SOURCE:** 35 Watt High Intensity Discharge Xenon lamp with 2000 hour minimum lifetime.

LIGHT OUTPUT: 35 Watt High Intensity Discharge Xenon lamp in a deep-dish parabolic reflector produces a

long range high intensity beam with optimum peripheral illumination for scene lighting. Fully

articulating head can be aimed precisely at target.

Xenon H.I.D. Lamp Rating: 3350 Lumens typical with 1,000,000 Peak Beam Candlepower.

ON/OFF: Toggle switch allows operation from internal battery or continuous operation from external

12VDC power source.

**RUN TIME:** 1.75 hours per charge. All models include a 10 foot 12VDC external power cord for continuous

operation.

BATTERY: Zero-maintenance 12V, 7.2Ah sealed lead acid and is rechargeable up to 500 times using

existing LiteBox® system charge racks. Red and green LEDs provide charge status feedback. 10 hour charge to 90% battery capacity with continuous trickle charge to maximize battery capacity. HID LiteBox® battery will continue to charge while operating directly from an

external 12V DC power source when using the remote cord.

MODELS: Standard System - International safety orange or black; includes shoulder strap; comes with AC

and DC chargers, 10ft 12VDC power cord, charge rack and flood lens; ideal for field

maintenance, inspection of construction sites and remote equipment.

Vehicle Mount System - International safety orange or black; comes with vehicle-mountable hard-wire rack, 10ft 12VDC power cord, flood lens and shoulder carrying strap; ideal for

military operations and general scene lighting.

**FEATURES:** 1,000,000 peak beam candlepower for long range applications.

Serialized for positive identification.
Fits existing Streamlight LiteBox® chargers.

**APPROVALS:** ( Meets applicable European Community Directives.

NFPA Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position.

(BC) CEC compliant

**WARRANTY:** Streamlight's Limited Lifetime Warranty.

OPTIONAL

ACCESSORIES: 100V, 230V, or 240V AC (home) and 12V DC (automobile) charger cords.

Locking charge rack; Quick release shoulder/waist strap.

IR pass filter; flood lens.

Issued: 12/22/2006 Revised: 12/21/2016 Rev: 2