

DUALIE® 3AA COLOR-RITE® ATEX ATEX RATED FLASHLIGHT WITH COLOR-RITE TECHNOLOGY®



Material/Lens Impact and chemical resistant Engineered Polymer resin; gasket-sealed and vented. Unbreakable polycarbonate facecap.

Antistatic body and integrated & retained facecap lock.

Length: 7.00 in. (17.78 cm) Facecap diameter: 1.86 in. (4.72 cm) Dims/Weight Body thickness: 1.06 in. (2.69 cm) Body Width: 1.52 in. (3.86 cm)

6.6 oz. (187 grams) with AA alkaline batteries, 5.7 oz. (162 grams) with AA lithium batteries*

Light Source/ Output

One high-power white LED, impervious to shock with a 50,000 hour lifetime. One 90 CRI LED, impervious to shock with a 50,000-hour lifetime. Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination. Flood beam produces a soft, wide beam to illuminate your work area. Spot and flood beams intersect for an uninterrupted light pattern to eliminate blind spots.

Features two white LEDs and three output modes: spot, flood, spot/flood combo:

- Spot: 225 lumens; 179m beam; runs 8 hours

- Uses a 90 CRI LED (4,000K) for true color recognition

- Spot/Flood Combo: 320 lumens: 167m beam: runs 5 hours

Switch Opposing head switches for easy identification. Spot LED push button head switch provides one handed momentary or constant operation.

Flood LED push button head switch provides on/off operation.

Battery Three (3) "AA" size alkaline or lithium primary batteries. Mechanical battery polarity protection.

- IP67 - dust-tight; waterproof to 1m for 30 minutes; 2m impact resistance tested Features

- One-handed operation of all lighting modes

- Integrated, non-protruding spring-loaded belt clip contained within the body outline

- Corrosion-proof

ATEX/IECEX: II 1G Ex ia op is IIC T3/T4 Ga; FTZU 15ATEX0221X, IECEx FTZU 16.0017X

InMetro: Ex ia op is IIC T3/T4 Ga; DNV 22.0153X

Meets applicable United Kingdom and European Community Directives









Warranty

Approvals

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information. Visit streamlight.com for full warranty information.

Description	UPC	Part #
Dualie 3AA Color-Rite - includes 3 "AA" alkaline batteries - Orange ATEX	080926-68915-2	68915
Dualie 3AA Color-Rite - includes 3 "AA" alkaline batteries - Orange INMETRO	080926-68918-3	68918

68089 Poly Mount Kit universal mounting via slot attachment or self-adhesive mount









Clips onto hard hats



Description	UPC	Part #
4AA/3AA Helmet Mount	080926-68085-2	68085
4AA/3AA Gallet mount	080926-68086-9	68086
Poly Mount Kit	080926-68089-0	68089
Rubber Helmet Strap	080926-99075-3	99075