

DECISION MAKING TIC FOR FIREFIGHTING. **DURABLE, HIGH-RESOLUTION** THERMAL IMAGING CAMERA.

KEY CAMERA SPECS

320 x 240 Thermal Sensor

57° Horiz Field of View

-20C (-4F) to 550C (1022F) Temp Detection

IP67 Ingress Protection

High Impact and Heat Resistant

300 Lumen LED Flashlight



thermal.com



Designed with firefighters for firefighters, the AttackPRO™ thermal imaging camera offers an unmatched combination of image quality, durability, and price.

With its high resolution and wide field of view, AttackPRO is the new decision-making weapon of choice for captains and commanding officers. Mixed-gain pixel technology eliminates the visual confusion and delay of switching between highgain and low-gain modes. AttackPRO lets you clearly see the fire and the crew, all in one detailed image.

The kit includes the AttackPRO camera, 2 batteries, and a charging dock.



Designed and Manufactured in the USA with Global Components. Thermal sensor designed and manufactured by Seek in Santa Barbara, CA USA



AttackPRO Kit: FQ-PAEX 5yr Enhanced Warranty: WA-5USATTACKPRO

KEY FEATURES

320 x 240 High-Resolution Thermal Sensor

76,800 temperature pixels for maximum image clarity and sensitivity

Waterproof Design

Durable and reliable design built with IP67 rating

Wide, 57-Degree Field of View

Easily scan a large area to identify hazards or victims in seconds

Long-Lasting Rechargeable Battery

Greater than 6 hours of continuous thermal imaging

Simple Operation. Purpose-Built for the Fire Gound

One button thermal operation, no confusing menus or settings, Get the job done efficiently and consistently

BENEFITS

Decision Making on Command

Direct Firefighters, water, and resources with expedited tactical precision

Robust Personal TIC

Equip the entire department with the first affordable decision making TIC

See Through Smoke. Flashight Optional.

300 lumen LED flashlight available at the touch of a button

Search and Rescue

Find victims and self-rescue faster with a reliable personal TIC

Execute 360 Size-ups & Overhaul Faster

When seconds count, a Seek decision-making TIC saves time and lives





TECHNICAL SUMMARY

SPECIFICATIONS	DESCRIPTION
Thermal Sensor	320 x 240 (76,800 pixels)
Detection Distance	12 inches to 1,000 feet
Field of View	57° HFOV, 42° VFOV
Temperature Range	-4 to 1,022°F (-20 to 550°C)
Operating Temp	-4 to 131°F (-20 to 55°C) - no time limit
	up to 302°F (150°C) - max 15 min
	up to 500F° (260°C) - max 5 min
Frame Rate	> 25 Hz Fast Frame
IP Rating	IP67 Waterproof
Flashlight	300 Lumen LED
Display	3.5" Color with Corning® Gorilla® Glass
Thermal Sensitivity	< 70 mK
User Interface	On device 2 tactile button operation
Temp. Display Scale	Fahrenheit or Celsius
Image modes	2 Options (TIBASIC-default, and TIBASIC+)
Storage Media	NA
Battery	>6 Hours Thermal Imaging (w/o flashlight); >3hr.

For support and user guides visit thermal.com

(with thermal AND flashlight)

300 LUMEN LED LIGHT



Seek AttackPRO combines powerful thermal insight and a bright LED flashlight in an intuitive, two button interface.

USER INTERFACE





TI BASIC


Maintain your situational awareness with a simple and decluttered display showing greyscale and colorized regions

TI BASIC+

Enhance your tactics with a spot temp readout while still maintaining greyscale and colorized regions

THERMAL APPLICATIONS

Battery



360 SIZE UP



FIRE ATTACK



OVERHAUL













Seek more at thermal.com