

## MT-220 Mini-TAC Pro

<b>MARKET APPLICATIONS</b>	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
<b>DESCRIPTION</b>	This non-rechargeable Mini-TAC Pro light uses an LED and has a deep parabolic reflector creating a tight, long throw beam for distance illumination. With a waterproof design, it is constructed from aircraft-grade 6061-T6 aluminum with a Type III hard anodized finish. The tail switch provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. The light come with a removable pocket clip and is powered by two included AA batteries. Meets requirements of NFPA-1971-8.6 (2013).
<b>CASE MATERIAL</b>	Aircraft-grade 6061-T6 Aluminum with a Type III Hard Anodized Finish - Black
<b>DIMENSIONS</b>	Length: 6 inches (152 mm) • Handle diameter: 0.6 inches (15 mm) • Head diameter: 0.9 inches (23 mm)
<b>WEIGHT</b>	Weight: 3.2 oz. (91 g) with batteries installed.
<b>LENS</b>	Unbreakable polycarbonate with scratch resistant coating.
<b>LIGHT SOURCE</b>	LED. Impervious to shock with a 50,000 hour lifetime.
<b>LIGHT OUTPUT</b>	High - 265 lumens, Medium - 130 lumens, Low - 90 lumens
<b>ON/OFF</b>	Single Tail Cap Switch - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe
<b>RUN-TIME</b>	High - 2.5 hours, Medium - 8 hours, Low - 18 hours
<b>BATTERY</b>	2 AA Premium Batteries (included)
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• LED technology – 50,000+ hours</li> <li>• Momentary or constant-on, plus 3 user-selectable brightness settings plus strobe</li> <li>• Sharp focused flashlight beam</li> <li>• Aircraft-grade 6061-T6 aluminum housing</li> <li>• Type III hard anodized finish</li> <li>• Non-slip grip</li> <li>• Waterproof</li> <li>• Impact and chemical resistant</li> <li>• Meets requirements of NFPA-1971-8.6 (2013)</li> <li>• Powered by 2 AA batteries (included)</li> </ul>

**WARRANTY** Limited Lifetime Warranty  
**APPROVALS**



FL 1 STANDARD	HIGH	MEDIUM	LOW
	<b>265</b> LUMENS	<b>130</b> LUMENS	<b>90</b> LUMENS
	<b>2h 30min</b>	<b>8h</b>	<b>18h</b>
	<b>100m</b>	<b>73m</b>	<b>56m</b>
	<b>2486cd</b>	<b>1335cd</b>	<b>797cd</b>
			
			

**MT-220 PERFORMANCE CURVE**

